

# HL-UPS HIGH FREQUENCY ONLINE 3KVA - 3C20KS

UPS MODEL	HL-6K	HL-6KS	HL-10K	HL-10KS	HL-3C15KS	HL-3C20KS			
Rated capacity	6KVA/4.8KW		10KVA/8KW		15KVA/12KW				
<b>INPUT</b>									
Wire method	Single phrase or three phase earth ground								
Rated voltage	220VAC			380VAC					
Normal Voltage	120VAC - 275VAC ±5								
Rated Freq	50HZ								
Frequency Range	(45- 55)HZ±0.5HZ								
Bypass range	187VAC-264VAC								
<b>BAT</b>									
Rated bat Voltage	192VDC								
Battery capacity*Quantily	12VDC/7.2Ah*16PCS			12VDC*16PCS					
<b>AC OUTPUT</b>									
Output system	Single phrase & earth ground								
OutPut voltage	220VAC±3%								
Output frequency	50HZ±1%								
Dynamic voltage transient range	<5%								
Dynamic transient restore	<60ms								
Waveform	Sine ware THD<3%(linear load) Sine ware TDH<8%(nonlinear load)								
Input power factor	0.8								
Overload capability	105%-125% 30s to Bypass								
Communications	RS232(turn to 485), Intelligelt slot								
<b>Net weight</b>									
Dimensions	240*500*460mm			248*500*616					
<b>Environmental</b>									
Ambient temperature	-10°C - +40°C								
Altitude	Lower than 1000m: no derating Over 1000m: 1% derating for every 100m rise								
Storage temperature	-15°C - + 45°C								

HL -UPS ONLINE TỪ 6KVA - 20KVA ĐƯỢC BẢO HÀNH 36 THÁNG CHO BỘ XỬ LÝ VÀ 24 THÁNG CHO ÁC QUY

